



TORO® DINGO® TX 1300

COMPACT UTILITY LOADERS

Ideal for landscape, hardscape and tree care jobs, the TX 1300 brings a new combination of power, reach and convenient control to the Toro® Dingo® lineup. With a 37 hp Yanmar® Tier IV diesel engine and 1,300 lbs of rated operating capacity, it's the user-friendly workhorse you need to save time. The exclusive INTELESCOPE® loader arm with SmartLoad adds 26" of reach, and the telescoped hinge-pin height of 109" means you can lift loads up and over the side of a dumpster or truck for maximum productivity. Plus, you can operate the Toro patented traction controls with one hand and thumb-controlled telescoping extension and auxiliary functions (in the loader arm control) with the other to pick, place and dump materials with ease all day long.

FEATURES



INTELESCOPE LOADER ARM

Featuring SmartLoad for a hinge-pin height of 109" which adds 26" of reach over other compact utility loaders



OUTSTANDING ROC

The durable loader arm with improved q-tach casting, allows for a more durable loader arm design and up to 1,300 lbs of operating capacity



QUICK COUPLER SYSTEM

Pressure relieving quick coupler system makes connection of attachments easier



EASE OF USE

Toro patented traction control and integrated hydraulic operation in loader arm control



AUXILIARY PEDAL

User friendly auxiliary pedal on an enlarged operator platform improves ease of engagement



TORO® DINGO® TX 1300

SPECIFICATIONS

DINGO TX 1300 (MODEL 22370)		
ENGINE	Engine	37 HP (27 kW) Yanmar® diesel
	Air Filter	Remote dual element
	Cooling System	Combo downflow radiator and oil cooler, independent fuel cooler
	Fuel Tank	11 gallons (42 liters)
	Oil Capacity	5 quarts (4.7 liters)
HYDRAULIC SYSTEM	Hydraulic Pressure	3,200 PSI (22,063 kPa)
	Hydraulic Flow	Traction: 13.4 gpm (each pump) Auxiliary: 14.3 gpm
	Reservoir Capacity	9.2 gallons (34.8 liters)
TRACKS	Standard	MERT track with "TF" style tread
	Traction	Dual hydrostatic pump
DIMENSIONS	Track Dimensions	126.6" x 9.1" (321.5 cm x 23.1 cm)
	Wheelbase	39" (99.0 cm)
	Ground Clearance	5.9" (14.9 cm)
	Overall Dimensions (WxLxH) With Bucket	46" x 103.1" x 56.5" (116.8 x 261.8 x 143.5 cm)
	Overall Dimensions (WxLxH) Without Bucket	46" x 84.9" x 56.5" (116.8 x 215.6 x 143.5 cm)
	Maximum Operating Height	133" (337.8 cm)
	Hinge Pin Height	109.2" (277.3 cm) - extended 89.4" (227.0 cm) - retracted
	Dump Height	90.7" (230.3 cm) extended 70.9" (180.0 cm) retracted
	Dump Angle	38-degrees
	Reach - Fully Raised	26.7" (67.8 cm)
	Ground Speed	4.7 mph (7.6 km/h)
	Weight	3,858 lbs (1,749.9 kg)
	Rated Operating Capacity (35% of Tip Capacity)*	618 lbs (280.3 kg) - extended 1,300 lbs (589.6 kg) - retracted
	Ground Pressure	5.5 PSI

*Per ISO 14397-1

