

TOTEM HEATERS

MODELS 10CD // 5CD // 5CDLT // IHS700



TOTEM 10CD

1,000,000 BTU INDIRECT HEATER TRAILER



SPECIFICATIONS

OPERATING SPECIFICATIONS

- One Million BTU (500,000x2)
- 30+ Hours Running Time (full load)
- 8 GPH Maximum – 250 gallon fuel capacity
- 100% Spill Containment with in-floor fuel tank
- 33% Smaller than previous models

HEATER SYSTEM

- Indirect Fired for clean heated air
- 4 each 12" ducted heat outlets (OPLT. dual 16" outlets)
- UL and CSA listed heaters
- Arctic proven design

GENERATOR

- Kubota liquid-cooled 1800 rpm
- 10 kW Prime Power Rating
- 2 – 500 watt halogen flood lights
- Safety shutdown on engine
- Easy access for service

WEIGHT AND DIMENSIONS

Overall Height (highest point) 88.5 inches (224cm)
Overall Length (with tongue retracted) 128 inches (386cm)
Overall Width (widest point) 94 inches (233cm)
Weight (Operating) 4900 pounds (1547kg)
Dry Shipping Weight 3510 pounds
Air Cargo dims* 119"L x 76.5"H x 92"W (302cm x 187cm x 243cm)

*Unit is equipped with a retractable trailer tongue for ease of loading and smaller cubic space. Removable fenders available by request. Ask for details.

Rental units are available by the day, week or month. Ask about financing and our in-house lease purchase programs. All units are available for purchase.

TOTEM 500

500,000 BTU INDIRECT HEATER TRAILER



SPECIFICATIONS

OPERATING SPECIFICATIONS

- 500,000 BTU + 3100 CFM
- 25 Hour continuous running time (full load)
- 4.3 GPH maximum – 120 gallon fuel capacity

HEATER SYSTEM

- Indirect fired for clean heated air
- 2 each 12" ducted heat outlets (OPT. dual 16" outlets)
- Over-temp and flame detection safety shutdown
- UL and CSA listed heater

GENERATOR

- Northern Lights liquid cooled diesel engine
- 6 kW continuous duty prime power rating
- Safety shutdowns on engine
- Easy access for service
- Exterior receptacles for on-site power use

WEIGHT AND DIMENSIONS

Overall Height (without exhaust) 64 inches (162cm)
Overall Length (with tongue retracted) 73 inches (130cm)
Overall Width (widest point) 78 inches (198cm)
Weight (Operating) 3100 pounds (1400kg)
Dry Shipping Weight 2400 pounds (1090kg)
Air Cargo dims* 74"L x 64"H x 72"W (188cm x 162cm x 183cm)

*Unit is equipped with a retractable trailer tongue for ease of loading and smaller cubic space. Removable fenders available by request. Ask for details.

Rental units are available by the day, week or month. Ask about financing and our in-house lease purchase programs. All units are available for purchase.

TOTEM 5CDLT

HEATER / LIGHT TOWER 500,000 BTU



SPECIFICATIONS

OPERATING SPECIFICATIONS

- 500,000 BTU + 3100 CFM
- 100% fuel containment
- 28 hour continuous running time (full load)
- 4.3 GPH maximum - 120 gallon fuel capacity
- Removable / extendable light tower
- 4 each 1000 watt halide lights

HEATER SYSTEM

- Indirect fired for clean heated air
- 2 each 12" ducted heat outlets (OPT. dual 16" outlets)
- Over-temp and flame detection safety shutdown
- UL and CSA listed heater

GENERATOR

- 10 kW Kubota / Onan power plant
- Extra 110v and 220v power receptacles
- Safety shutdowns on engine
- Easy access for service

- Exterior receptacles for on-site power use

WEIGHT AND DIMENSIONS

16.5' Tower Height

Shipping dims (light tower on) 93"L x 80"W x 100"

Shipping dims (light tower off) 93"L x 80"W x 80"

Shipping Weight with tower 2,600 pounds

TRAILER

Highway towable

DOT light package

Interior light

Leveling jack all 4 corners


Forklift pockets

Rental units are available by the day, week or month.

Ask about financing and our in-house lease purchase programs. All units are available for purchase.

TOTEM IHS700

700,000 BTU INDIRECT HEATER TRAILER



SPECIFICATIONS

OPERATING SPECIFICATIONS

- 700,000 BTU indirect fired heater
- 20 kW Kubota/Onan continuous duty diesel generator
- 120 volt and 240 volt accessory outlets
- Dual fuel tanks: 250 gal. heater / 45 gal. generator
- 35 hour continuous run time

HEATER SYSTEM

- 409 stainless steel high efficiency fire-tube burner
- 5 HP belt driven 4,600 cfm reverse incline blower
- 2 - 16" ducting inlet and return-air outlets
- Over-temp and flame detection safety shutdowns
- Stack robber auto damper maintains outlet temperature

TRAILER

- Steel enclosure with complete fluid containment
- Picking eyes and forklift pockets
- 2 - 500 watt halogen lights
- Highway towable with DOT lighting package

WEIGHT AND DIMENSIONS

Overall Height (highest point) 88.5 inches
Overall Length (with tongue retracted) 168 inches
Overall Width (widest point) 102 inches
Weight (Operating) 6,800 pounds

NEW FEATURE // Oilmate Management System

Eliminate oil disposal problems. Oilmate continually injects clean oil into engine reservoir while burning used oil. Maintain optimal performance of oil system while nearly eliminating oil changes.

- EPA CERTIFIED
- 4,000 HOUR INTERVALS

Rental units are available by the day, week or month. Ask about financing and our in-house lease purchase programs. All units are available for purchase.



TOTEM'S HEATER LINE-UP

	TOTEM 10CD	TOTEM 5CD	TOTEM 5CDLT	TOTEM IHS700
DUCTING				
12"X25'	2 EACH STD	2 EACH STD	2 EACH STD	N/A
16"X25'	2 EACH OPT	1 EACH OPT	1 EACH OPT	2 EACH STD
Insulated Ducting	OPT	OPT	OPT	OPT
LIGHTING				
External	2 EACH 500 WATT STD	1 EACH 500 WATT STD	OPT	2 EACH 500 WATT STD
Internal	1 EACH 100 WATT STD	1 EACH 100 WATT STD	1 EACH 100 WATT STD	2 EACH 100 WATT STD
16' Tower	OPT	N/A	STD	OPT
DOT Light Package	OPT	OPT	OPT	OPT
Operating Beacon	OPT	OPT	OPT	OPT
GENERATOR				
6 kW Luger	N/A	STD	N/A	N/A
7.5 kW Kubota	N/A	OPT	N/A	N/A
10 kW Kubota	STD	N/A	STD	N/A
12 kW Kubota	OPT	N/A	OPT	OPT
20 kW Kubota	OPT	N/A	N/A	STD
ADDITIONAL OPT				
Spare Tire	OPT	OPT	OPT	OPT
Fire Extinguisher	OPT	OPT	OPT	OPT
External Emergency Stop Button	OPT	OPT	OPT	OPT
Fluid Containment	STD	STD	STD	STD
Fork Pockets	STD	STD	STD	STD
Oilmate System	OPT	OPT	OPT	OPT
Gas Detection Shutdown	OPT	OPT	OPT	OPT
Skid Mount	OPT	OPT	OPT	OPT
Drop Axles	OPT	OPT	OPT	OPT
HiStatic Pressure	OPT	OPT	OPT	STD
Air Compressor	OPT	OPT	OPT	OPT
Remote Thermostat	OPT	OPT	OPT	OPT



If you can dream it, we can build it!

TOTEM
EQUIPMENT & SUPPLY, INC.

2536 Commercial Drive Anchorage AK 99501

P 907.276.2858 F 907.258.4623

www.toteminc.com

