

HEAT KING

HK 600 MOBILE GLYCOL HEATING SYSTEM



FEATURES

- 8-700FT HOSES
- THAW UP TO 11,200 FT²
- CURE UP TO 22,400 FT²
 - 605,000 BTU/HR
- UP TO 60 HRS RUN TIME
 - CSA/UL CERTIFIED
- PLC CONTROLLED SYSTEM
- BI-DIRECTIONAL POWERED REEL WITH FREEWHEEL FEATURE
- ON BOARD AIR COMPRESSOR




DOUBLE LOOP TECHNOLOGY

By using shorter hoses, more fluid, and higher efficiency pumps with increased flow, the Heat King provides more consistent temperature to the field for better concrete curing and ground thawing results.



HEAT KING ADVANTAGE



- GLYCOL GETS UP TO OPERATING TEMPERATURE FASTER THAN COMPETITORS (DESIGNATED CIRCULATION PUMP PULLS FROM THE RESERVOIR AND DOESN'T HAVE TO PUSH COLD GLYCOL THROUGH THE FIELD HOSES)
- GLYCOL CAN BE BLOWN OUT OF THE FIELD HOSES AND STORED IN THE RESERVOIR, ELIMINATING THE NEED TO STORE IT IN A CONTAINER. CONVENIENT WHEN ABANDONING THE HOSES IN CONCRETE OR FOR SPACE HEATING SET-UPS & TAKE DOWNS
- TYING INTO EXISTING MANIFOLDS SUCH AS IN-FLOOR HEATING
- OIL & GAS APPLICATIONS SUCH AS TANK HEATING & HAVING THE ABILITY TO RETRIEVE THE GLYCOL FROM STEAM COILS
- GLYCOL CAN BE LEFT IN THE FIELD HOSES OR THE RESERVOIR

HK600 SPECIFICATIONS

• Hose	8 - 700 ft Field Hoses (5/8" Hose)	• Interior Lights	Standard for ease of night operation
• Hose	Unspool with one person	• Mud Tray	Added under the reel to catch mud debris
• Supply Manifold	8 - 1/2" quick connect & 2 - 1 1/4" Camlock	• Heater Capacity Diesel	605,000 BTU/H Heating Fuel Input
• Return Manifold	8 - 1/2" quick connect & 2 - 1 1/4" Camlock	• Burner	Beckett Burner
• Ground Thawing Capacity	up to 11,200 ft ²	• Heater Capacity LP/NG	417,000 BTU/H (LP) 351,000 BTU/H (NG)
• Concrete Curing Capacity	up to 22,400 ft ²	• Glycol Tank	130 US GAL
• Temporary Heating Capacity	15,000 ft ² (Varies with R-Value)	• Electrical Requirements	2 - 120V AC 20A Circuits
• Field Pump	1 Hp Centrifugal	• Generator (Optional)	1 - 7,000W
• Circulating Pump	1/2 Hp Centrifugal	• LP/NG Units (Optional)	60 gallon Fuel Tank for Generator
• Fuel Tank	192 US GAL	• Axle	1 - 8,000lb Torsion Axle, Electric Brakes
• Run Time	Up to 60 Hours	• Hitch	2 5/16" Ball (Pintle also available)
• Fuel Consumption	HK 600 = 4.44 GPH, Genset = .55 GPH	• Dimensions	165"x75"x84" (Including Heater Vent)
• Flo Indicator	Ensures proper operation	• Weight (Fuel/Full)	9070 lbs
		• Weight (LP/NG Unit)	9,070 lbs

WWW.HEAT-KING.CA



Tamarack Industries